

## 15. Charging System/Alternator

|                                     |      |                                 |      |
|-------------------------------------|------|---------------------------------|------|
| Service Information                 | 15-1 | Regulator/rectifier Inspection  | 15-5 |
| System Location                     | 15-2 | Alternator Inspection           | 15-5 |
| Troubleshooting                     | 15-3 | Alternator Removal/Installation | 15-6 |
| Regulated Voltage/Ampere Inspection | 15-4 |                                 |      |

### Service Information

#### GENERAL WARNING

- The battery gives off explosive gases; keep sparks, flames, and cigarettes away. Provide adequate ventilation when charging or using the batteries in an enclosed space.
- The battery contains sulfuric acid (electrolyte). Contact with skin or eyes may cause severe burns. Wear protective clothing and a face shield.
  - If electrolyte gets in your skin, flush with water.
  - If electrolyte gets in your eyes, flush with water for at least 15 minutes and call a physician immediately.
- Electrolyte is poisonous. If swallowed, drink large quantities of water or milk and follow with milk of magnesia or vegetable oil and call a physician.
- KEEP OUT OF REACH OF CHILDREN.

#### CAUTION:

- Some electrical components may be damaged if terminals or connectors are connected or disconnected while the ignition switch is ON and current is present.
- The battery on this motorcycle is a sealed type. Do not try to remove the filler hole caps even during charging. Do not use a non-sealed battery as a replacement.

#### NOTE

- Refer to the instructions in the Operation Manual for the HONDA Battery Tester and Christie Battery Charger for detailed battery charging steps.
- The maintenance free battery must be replaced when it reaches the end of its service life.

- Quick charge a battery only in an emergency. Slow-charging is preferred.
- Remove the battery from the motorcycle when charging. If the battery must be charged on the motorcycle, disconnect the battery cables.
- When inspecting the charging system, check the system components and lines step-by-step according to the troubleshooting on page 14-3./5-3
- The following colour codes used are indicated throughout this section and on the wiring diagram.
 

|          |               |                |          |
|----------|---------------|----------------|----------|
| Bu=Blue  | G=Green       | Lg=Light green | R=Red    |
| Bl=Black | Gr=Gray       | O=Orange       | W=White  |
| Br=Brown | Lb=Light blue | P=Pink         | Y=Yellow |
- Always turn off the ignition switch before disconnecting any electrical component.
- For extended storage, remove the battery, give it a full charge, and store it in a cool, dry place.
- For battery remaining in an stored motorcycle, disconnect the negative battery cable from the battery terminal.
- Immediately wash off any spilled electrolyte.

※ 7-7) - バッテリー 充電方法  
(PC500)