

## Left Handlebar Disassembly/Assembly

## WARNING

• Contaminants in the system may cause a reduction or loss of braking ability.

## CAUTION:

• Spilled brake fluid will damage painted, plastic, or rubber parts.

Procedure		Q'ty	Remarks
(1)	Disassembly Order	1	Disconnect from the switch terminal.  Disconnect the cable from the choke lever. Only loosen.
(2)	Left rear view mirror	2	
(3)	Clutch switch cable	2	
(4)	Clutch lever holder bolt	1	
(5)	Clutch lever holder	1	
(6)	Clutch lever bracket	2	
(7)	Mounting screw	1	
(8)	Left handle switch housing	1	
(9)	Choke cable	1	
(10)	Handle pinch bolt	2	
(11)	Stop ring	1	
(12)	Left handlebar	1	
(13)	Bolt/left handle weight	1/1	
(14)	Left handle grip	1	
(14)	Choke lever	1	
(14)	Assembly Order	1	Align the pin on the handlebar with the top bridge slot.  Connect the cable to the choke lever. Align the locating pin on the switch housing with the hole in the handlebar. Tighten the front screw first.  • Install the holder with its "UP" mark facing up. • Align the end of the holder with the punch mark on the handlebar.  Tighten the upper bolt first. Connect to the switch terminal.
(13)	Choke lever	1	
(12)	Left handle grip	1	
(11)	Left handle weight/bolt	1/1	
(10)	Left handlebar	1	
(9)	Stop ring	1	
(8)	Handle pinch bolt	2	
(7)	Choke cable	1	
(6)	Left handle switch housing	1	
(5)	Mounting screw	2	
(4)	Clutch lever bracket	1	
(3)	Clutch lever holder	1	
(2)	Clutch lever holder bolt	2	
(1)	Clutch switch cable	2	
(1)	Left rear view mirror	1	