

Requisite Service

• Brake fluid draining/air bleeding

Procedure		Q'ty	Remarks
Disassembly Order			
(1)	Bracket	1	
(2)	Bracket retainer	1	
(3)	Pad pin plug	1	
(4)	Pad pin	1	
(5)	Pad	2	
(6)	Pad shim	1	
(7)	Collar	1	
(8)	Boot	1	
(9)	Boot	1	
(10)	Bleeder/cap	1/1	
(11)	Pad spring	1	
(12)	Caliper piston	1	
(13)	Dust seal	1	
(14)	Piston seal	1	CAUTION: • Be careful not to damage the piston sliding surface.
Assembly Order			
(14)	Piston seal	1	
(13)	Dust seal	1	
(12)	Caliper piston	1	
(11)	Pad spring	1	Install the spring as shown.
(10)	Bleeder/cap	1/1	
(9)	Boot	1	
(8)	Boot	1	
(7)	Collar	1	
(6)	Pad shim	1	Install onto the piston side pad.
(5)	Pad	2	
(4)	Pad pin	1	Apply a thin coat silicone grease on the threads.
(3)	Pad pin plug	1	
(2)	Bracket retainer	1	
(1)	Bracket	1	Assemble the bracket and the caliper, making sure that the front boot is seated in the groove properly.