

## Torque Values

| Standard<br>Fasteners Type | Torque            | Fasteners Type            | Torque            |
|----------------------------|-------------------|---------------------------|-------------------|
|                            | N·m (kg·m, ft·lb) |                           | N·m (kg·m, ft·lb) |
| 5 mm hex bolt and nut      | 5 (0.5, 4)        | 5 mm screw                | 4 (0.4, 3)        |
| 6 mm hex bolt and nut      | 10 (1.0, 7)       | 6 mm screw, SH bolt       | 9 (0.9, 7)        |
| 8 mm hex bolt and nut      | 22 (2.2, 16)      | 6 mm flange bolt and nut  | 12 (1.2, 9)       |
| 10 mm hex bolt and nut     | 35 (3.5, 25)      | 8 mm flange bolt and nut  | 27 (2.7, 20)      |
| 12 mm hex bolt and nut     | 55 (5.5, 40)      | 10 mm flange bolt and nut | 40 (4.0, 29)      |

\*Torque specifications listed below are for important fasteners.

\*Others should be tightened to standard torque values listed above.

NOTE: 1. Apply sealant to the threads.

2. Apply a locking agent to the threads.

3. Apply molybdenum disulfide oil to the threads and flange surface.

4. Left hand threads.

5. Stake.

6. Apply oil to the threads and flange surface.

7. Apply clean-engine oil to the O-ring.

8. Torque wrench scale reading using a special tool.

9. Apply grease to the threads and flange surface.

10. UBS bolt.

| Engine                         |    | Q'ty | Threads<br>dia (mm) | Torque<br>N·m (kg·m, ft·lb) | Remark      |
|--------------------------------|----|------|---------------------|-----------------------------|-------------|
| Item                           |    |      |                     |                             |             |
| Cylinder head cover bolt       |    | 8    | 6                   | 10 (1.0, 7.2)               |             |
| Camshaft holder bolt           |    | 4    | 6                   | 12 (1.2, 9)                 |             |
|                                | IN | ✓ A  |                     |                             | NOTE 10     |
|                                |    | ✓ B  | 8                   | 23 (2.3, 17)                | 6x40mm      |
|                                |    | ✓ C  | 4                   | 36 (3.6, 26)                | NOTE 10     |
|                                |    |      |                     |                             | 8x130mm     |
|                                |    |      |                     |                             | NOTE 10     |
|                                |    |      |                     |                             | 8x151mm     |
|                                | EX | D    | 4                   | 12 (1.2, 9)                 | flange bolt |
| Cylinder head bolt             |    | E    | 4                   | 36 (3.6, 26)                | 6x43mm      |
| Cam sprocket bolt              |    |      | 8                   | 19 (1.9, 14)                | NOTE 10     |
| Spark plug                     |    | 2    | 10                  | 12 (1.2, 9)                 | 8x80mm      |
| Connecting rod bearing cap nut |    | 4    | --                  | 24 (2.4, 17)                | NOTE 2      |
| Shift drum center bolt         |    | 1    | --                  | 23 (2.3, 17)                |             |
| Flywheel bolt                  |    | 1    | 10                  | 85 (8.5, 62)                | NOTE 2      |
|                                |    |      |                     |                             | NOTE 10     |
|                                |    |      |                     |                             | 10x35mm     |
| Starter clutch bolt            |    | 1    | 10                  | 85 (8.5, 62)                | NOTE 10     |
|                                |    |      |                     |                             | 10x35mm     |
| Starter clutch cover bolt      |    | 3    | 8                   | 28 (2.8, 20)                | flange bolt |
|                                |    |      |                     |                             | 8x14mm      |
|                                |    |      |                     |                             | NOTE 2      |
| Clutch center lock nut         |    | 1    | 20                  | 65 (6.5, 47)                |             |
| Gear shift return spring pin   |    | 1    | 8                   | 25 (2.5, 18)                | NOTE 2      |
| Oil pump driven sprocket bolt  |    | 1    | 6                   | 15 (1.5, 11)                | NOTE 2      |
| Oil pressure switch            |    | 1    | --                  | 12 (1.2, 9)                 | NOTE 1      |
| Neutral switch                 |    | 1    | 10                  | 12 (1.2, 9)                 | NOTE 1      |
| Oil filter center bolt         |    | 1    | 20                  | 18 (1.8, 13)                |             |