

## Maintenance Schedule

Perform the PRE-RIDE INSPECTION in the Owner's Manual at each scheduled maintenance period.

I:Inspect and clean, Adjust, Lubricate or Replace if necessary.

C:Clean, R:Replace, L:Lubricate, A:Adjust

The following items require some mechanical knowledge. Certain items (particularly those marked \* and \*\*) require more technical information and tools. Consult your authorized Honda dealer.

Item	Frequency	Which ever Comes First ↓ Note	Odometer Reading (Note 1)								Refer to page (s)
			X1,000 km	1	6	12	18	24	30	36	
			X1,000 mi Months	0.6	4	8	12	16	20	24	
* Fuel Line											Note 5
* Throttle Operation											Note 5
* Carburetor Choke											3-
Air Cleaner		(Note 2)				R				R	3-5
Crankcase Breather		(Note 3)		C	C	C	C	C	C	C	Note 5
Spark Plug				I	R	I	R	I	R		Note 5
* Valve Clearance				I							3-9
Engine Oil				R		R		R		R	Note 5
Engine Oil Filter				R		R		R		R	3-7
* Carburetor Synchronization				I		I		I		I	3-8
* Carburetor Idle Speed				I		I		I		I	3-8
Radiator Coolant		(Note 4)								R	5-3
* Cooling System										I	Note 5
Drive Chain				Every 1,000 km (600 mi) I. L.							3-5
Brake Fluid		(Note 4)				R				R	Note 5
Brake Pad Wear						I				I	3-6
Brake System				I		I		I		I	Note 5
* Brake Light Switch						I		I		I	Note 5
* Headlight Aim						I		I		I	Note 5
Clutch System				I		I		I		I	Note 5
Side Stand											3-6
* Suspension						I		I		I	Note 5
* Nuts, Bolts, Fasteners				I		I		I		I	Note 5
** Wheels/Tires						I		I		I	Note 5
** Steering Head Bearings						I		I		I	Note 5

\*:Should be serviced by an authorized Honda dealer, unless the owner has proper tools and service data and is mechanically qualified. Refer to the official Honda service manual.

\*\* :In the interest of safety, we recommend these items be serviced only by an authorized Honda dealer.

Notes: 1. At higher odometer readings, repeat at the frequency interval established here.

2. Service more frequently when riding in unusually wet or dusty areas.

3. Service more frequently when riding in rain or at full throttle.

4. Replace every 2 years, or at indicated odometer interval, whichever comes first. Replacement requires mechanical skill.

5. Refer to Common Service Manual.