

~~Right Handlebar Disassembly/Assembly~~ 2

Procedure		Q'ty	Remarks
Disassembly Order			
(1)	Right rear view mirror	1	
(2)	Brake switch cable	2	
(3)	Master cylinder holder bolt	2	
(4)	Master cylinder holder	1	Disconnect the brake switch cable from the terminal.
(5)	Brake master cylinder	1	CAUTION: • Keep the master cylinder upright to prevent the air from entering the master cylinder.
(6)	Throttle cable	2	Disconnect the cable from the throttle grip.
(7)	Right handle switch housing	1	Remove the mounting screw.
(8)	Handle pinch bolt	2	Only loosen.
(9)	Right handlebar	1	
(10)	Bolt/right handle weight	1/1	
(11)	Throttle grip assembly	1	
Assembly Order			
(11)	Throttle grip assembly	1	
(10)	Right handle weight	1/1	
(9)	Right handle/stop ring	1/1	Align the pin on the handlebar with the top bridge slot.
(8)	Handle pinch bolt	2	
(7)	Right handle switch housing/screw	1/2	• Align the locating pin on the switch housing with the hole in the handlebar. • Tighten the front screw first.
(6)	Throttle cable	2	Connect to the throttle cable.
(5)	Brake master cylinder	1	
(4)	Master cylinder holder	1	• Install the holder with its "UP" mark facing up. • Align the end of the holder with the punch mark on the handlebar.
(3)	Master cylinder holder bolt	2	Tighten the upper bolt first.
(2)	Brake switch cable	2	Connect to the terminals.
(1)	Right rear view mirror	1	